



ARTISAN 2 DECK OVEN



Artisan Stone Deck Oven, Individual Programmable Control per Chamber, Individual Shot Steam per Chamber, Standard One Piece Shipment, Single Electrical Connection, Single Water & Drain Connection, Stainless Steel Construction, Multiple Deck Heights (6", 8", 10", 12"), 1" Thick Refractory Stone Deck, 99 Hour Delay-Start Timer, Standard Heavy Duty Legs with Casters, Economy Mode for Energy Saving



PROJECT _____

ITEM NO. _____

NOTES _____

MODEL NUMBER: **2 T**



*SHOWN IN 2T3

FEATURES

- Independent Baking Decks (up to 4) with Digital Control Panels
- Deck Capacity of 1, 2, 3 or 4 Pans
- Deck Heights
 - 6" (152mm)
 - 8" (204mm) STANDARD
 - 10" (254mm)
 - 12" (305mm)
- 600°F (316°C) Max Bake Temperature
- Independent Temperature Control for Upper & Lower Deck Elements, Plus Front Temperature Loss Control
- Independent Shot Steam Per Deck with Steam Box On/Off Control
- 99 Hour Delay Start Up Timer & Economy Mode

CONSTRUCTION

- Stainless Steel Construction
- 1" (25 mm) Refractory Stone Deck
- Single Point Connection for Electrical, Drain & Water
- Fully Insulated Illuminated
- Fully Retracting Doors (Save Space when Loading & Unloading)
- Legs with Swivel Casters (2 locking)
- One Piece Shipment

OPTIONS & ACCESSORIES

- Water Filter (50-1530)
- Standard Proofer for 1 - 2 Decks (ES2T)
- Low Profile Proofer for 3 Decks (ES2TP)
- Stainless Steel Deck
- Non-Functional Eyebrow Canopy (EH2T)
- Loaf Loader (LL)
- Single Phase Electrical
- 380-415V Electrical Configuration

CLEARANCES

- 1" (25mm) Sides & Back
- 6" (153 mm) Top

WARRANTY


- One Year Labor & Two Year Parts

PLEASE NOTE

- One Single Electrical Drain, Water Connection. Multiple Decks are inter-connected.
- Electrical Inlet located at the back on top right hand corner.
- For Steam Efficiency, use minimum water inlet pressure 50 PSI.
- To prevent steam system scale issues, install water softener rated for a minimum of 3 GPM.



2T - End Loaded





PROJECT _____

ITEM NO. _____

NOTES _____

MODEL NUMBER: **2 T**

DECK HEIGHT CONFIGURATOR

1. Optional Eyebrow Canopy



Dimensions: 5" H (128mm) x 54 1/2"W (1384mm) x 46 1/2" D (1181mm)

2. Top Cover Plate



Dimensions: 2 1/2" H (64mm) x 54 1/2"W (1384mm) x 46 1/2" D (1181mm)

3. Deck Choice #1 - 6" Internal Chamber Height



Exterior Dimensions: 13 5/8" H (347mm) x 54 1/2"W (1384mm) x 46 1/2" D (1181mm)

Interior Dimensions: 6" H (153mm) x 37 1/2"W (953mm) x 30" D (762mm)

4. Deck Choice #2 - 8" Internal Chamber Height



Exterior Dimensions: 15 5/8" H (397mm) x 54 1/2"W (1384mm) x 46 1/2" D (1181mm)

Interior Dimensions: 8" H (203mm) x 37 1/2"W (953mm) x 30" D (762mm)

5. Deck Choice #3 - 10" Internal Chamber Height



Exterior Dimensions: 17 5/8" H (447mm) x 54 1/2"W (1384mm) x 46 1/2" D (1181mm)

Interior Dimensions: 10" H (253mm) x 37 1/2"W (953mm) x 30" D (762mm)

6. Deck Choice #4 - 12" Internal Chamber Height



Exterior Dimensions: 19 5/8" H (497mm) x 35 3/4"W (908mm) x 46 1/2" D (1181mm)

Interior Dimensions: 12" H (303mm) x 37 1/2"W (953mm) x 30" D (762mm)

7. Base Plate



Dimensions:

2 1/2" H (64mm) x 54 1/2"W (1384mm) x 46 1/2" D (1181mm)

8. Standard Legs with Casters



Dimensions:

One Deck: 33" H (838mm) x 54 1/2"W (1384mm) x 37 1/2" D (952mm)

Two Deck: 24" H (610mm) x 54 1/2"W (1384mm) x 37 1/2" D (952mm)

Three Deck: 21" H (533mm) x 54 1/2"W (1384mm) x 37 1/2" D (952mm)

Four Deck: 9" H (227mm) x 54 1/2"W (1384mm) x 37 1/2" D (952mm)

9. Optional Proofer



Standard Proofer Dimensions (For 1 - 2 Chambers):

32 1/8" H (817mm) x 54 1/2"W (1384mm) x 37 1/2" D (953mm)

Shipping Weight: 590 lbs (268 kg)

Low Profile Proofer Dimensions (For 3 Chambers):

24 5/8" H (651mm) x 54 1/2"W (1384mm) x 37 1/2" D (953mm)

Shipping Weight: 590 lbs (268 kg)





PROJECT _____

ITEM NO. _____

NOTES _____

MODEL NUMBER: **2 T**

ELECTRICAL SYSTEM SINGLE PHASE

Model	Electrical System *ground wire not included						Water & Drain	Capacity (per deck)	
	Volts	Phase	Amps	kW	Hz	Wires		13"x18"	18"x26"
2T1	208	1	32	6.5	50/60	2	1/2" (12)	4	2
	240	1	28						
2T2	208	1	64	13	50/60	2	1/2" (12)	4	2
	240	1	56						
2T3	208	1	96	19.5	50/60	2	1/2" (12)	4	2
	240	1	84						
2T4	208	1	128	26	50/60	2	1/2" (12)	4	2
	240	1	112						

ELECTRICAL SYSTEM THREE PHASE

Model	Electrical System *ground wire not included						Water & Drain	Capacity (per deck)	
	Volts	Phase	Amps	kW	Hz	Wires		13"x18"	18"x26"
2T1	208	3	18	6.5	50/60	3	1/2" (12)	4	2
	240	3	16						
	480	3	8						
2T2	208	3	36	13	50/60	3	1/2" (12)	4	2
	240	3	32						
2T3	208	3	54	19.5	50/60	3	1/2" (12)	4	2
	240	3	48						
2T4	208	3	72	26	50/60	3	1/2" (12)	4	2
	240	3	64						

