



Brema Ice Machines add a touch of elegance to your establishment. Known and trusted in the industry for high-quality construction and consistent production, they are the most reliable choice for all your ice production needs.

# **Ice Pebbles**



Brema Pebble Ice Machines are preferred in bars, pubs, restaurants and night clubs for easy-melting ice. The combined action of an auger and extruder continuously produces ice for a consistent supply. The reliability of the inner working components ensures low operating costs and high efficiency ice production.



# Pebble Ice,

91% Dry

## **Standard Features**



1L water = 1kg ice



AISI 304 Stainless steel evaporator



Air cooling system



Easy cleanable internal rounded surfaces



Dust-proof water basin



RoHS Free



Electromechanical operation



ON/OFF switch



Automatic water charge



HFC Free HC R290 Refrigerant Gas



TB852A HC



TB1404A HC



# Brema Ice Machine Cleaner

For use with Brema Ice Machines to completely descale and clean interior and exterior surfaces and components. Colorless and odorless, powdered agent. Sold separately.

# **TB Series**

### Standard Features Included



Adjustable stainless steel feet



HCFC-Free insulated storage



Retractable insulated



TM140A HC



TM250A HC



BIN110



BIN200

## **TM Series**

Standard Features Included




 $1 \text{ m}^3 = 550 \text{ kg of ice}$ 



Frame in INOX






#### **TB852A HC**

120V, 500W, 4A	
_	
216 lbs	
207 lbs	
44 lbs	
26" x 19.5" × 27"	
130 lbs	
28.25" x 21.5" × 35"	
148 lbs	

Power Compatible With Production/24h\* Production/24h\*\* **Bin Capacity** Dimensions (L × W × H) Net weight Ship Dim. (L × W × H) Ship weight

## **TB1404A HC**

115V, 680W, 6A	
_	
333 lbs	
297 lbs	
88 lbs	
27.2" x 29.1" × 3	33.5"
130 lbs	
29" x 30.75" × 4	0"
220 lbs	




Adjustable feet 4 5/16" - 5 14/16"

- 1) WATER IN: 3 14/16" 6 4/16" 3/4"
- ② WATER OUT: 1 14/16" 5 15/16" 15/16"
- ③ ELECTRICAL CONNECTIONS: 3 7/16" 9 1/16"

- (1) WATER IN: 4 6/16" 6 14/16" 3/4"
- ② WATER OUT: 1 15/16" 5 2/16" 15/16"
- 3 ELECTRICAL CONNECTIONS: 6 2/16" 8 5/16"

#### **TM140A HC**



- 1 WATER IN: 3 3/16" 4 12/16" 3/4"
- 2 WATER OUT: 18 14/16" 2 9/16" 15/16"
- (3) ELECTRICAL CONNECTIONS: 2 11/16" 11 7/16"

**Compatible With** Production/24h\* Production/24h\*\* **Bin Capacity** 


Power

Dimensions (L  $\times$  W  $\times$  H) Net weight

Ship Dim. (L  $\times$  W  $\times$  H) Ship weight


#### **TM250A HC**

115V, 1170W, 10A
BIN200
540 lbs
500 lbs
_
22.4" × 22" × 27.4"
183 lbs
25.4" x 25.4" × 35.8"
205 lbs



- (1) WATER IN: 3 3/16" 4 12/16" 3/4"
- (2) WATER OUT: 18 14/16" 2 9/16" 15/16"
- (3) ELECTRICAL CONNECTIONS: 2 11/16" 11 7/16"

#### **BIN110**




TM140A HC 220 lbs 32" x 22" × 39.5" 117 lbs 34.5" x 24.5" × 46.25" 143 lbs Adjustable feet 3 15/16" - 6 15/16"

Power Compatible With Production/24h\* Production/24h\*\* **Bin Capacity** Dimensions (L × W × H) Net weight Ship Dim. (L  $\times$  W  $\times$  H) Ship weight

#### **BIN200**

TM250A HC 440 lbs 31" x 34" × 39.5" 163 lbs 33" x 36.25" × 47.5" 205 lbs



Adjustable feet 3 15/16" - 6 15/16"

\*Ambient Temperature 21°C (70°F) / Water 10°C (50°F) \*\*Ambient Temperature 32°C (90°F) / Water 21°C (70°F)







Warranty 3 years parts & labor, 5 years on the compressor