



Brema Ice Machines add a touch of elegance to your establishment. Known and trusted in the industry for high-quality construction and consistent production, they are the most reliable choice for all your ice production needs.

Ice Flakes



Brema Ice Flake Machines are used in retail, fish and seafood, and therapeutic sectors for chilled displays and presentations. The auger and ice breaker work together to create irregular shapes in a continuous fashion. The simplicity of the production process ensures cost-effective operation.



Granular Ice, 80-82% Dry

Standard Features



1L water = 1kg ice



AISI 304 Stainless steel evaporator



Air cooling system



Easy cleanable internal rounded surfaces



Dust-proof water basin



RoHS Free



Electromechanical operation



ON/OFF switch



Automatic water charge



HFC Free HC R290 Refrigerant



GB1504A HC



Brema Ice Machine Cleaner

For use with Brema Ice Machines to completely descale and clean interior and exterior surfaces and components. Colorless and odorless, powdered agent. Sold separately.

GB Series

Standard Features Included



Adjustable stainless steel feet



HCFC-Free insulated storage



Retractable insulated

GB903A HC





G280A HC



BIN200

G Series

Standard Features Included



 $1 \text{ m}^3 = 550 \text{ kg of ice}$



Rotation sensor on low speed shaft

G160A HC



Adjustable feet 4 5/16" - 5 14/16"

GB903A HC

115V, 450W, 4.5A
_
253 lbs
209 lbs
66 lbs
26" x 19.5" × 31.5"
148 lbs
29" x 30.75" × 40"
167.5 lbs

Power **Compatible With** Production/24h* Production/24h** **Bin Capacity** Dimensions (L \times W \times H) Net weight Ship Dim. (L × W × H) Ship weight

Power

Compatible With

Production/24h*

Production/24h** **Bin Capacity**

Dimensions (L \times W \times H)


Net weight

Ship Dim. (L × W × H)

Ship weight

GB1504A HC


115V, 680W, 15A
_
368 lbs
335 lbs
88 lbs
27" × 29" × 36"
187 lbs
29" x 30.75" × 46.5"
209 lbs



- ① WATER IN: 4 2/16" 7 3/16" 3/4"
- ② WATER OUT: 2 1/16" 6 14/16" 15/16"
- ③ ELECTRICAL CONNECTIONS: 3 10/16" 10"

- 1 WATER IN: 3 14/16" 6 4/16" 3/4" ② WATER OUT: 1 14/16" - 5 15/16" - 15/16"
- 3 ELECTRICAL CONNECTIONS: 3 7/16" 9 1/16"


G160A HC



- 115V, 665W, 5.8A BIN100 380 lbs 368 lbs 22.4" x 22" × 23.6" 139 lbs 25.4" x 25.4" × 32" 163 lbs
- (1) WATER IN: 3 3/16" 4 12/16" 3/4"
- (2) WATER OUT: 18 14/16" 2 9/16" 15/16"
- (3) ELECTRICAL CONNECTIONS: 2 11/16" 11 7/16"

G280A HC

120V, 1050W, 8.5A
BIN200
668 lbs
529 lbs
_
22" x 22" × 27 . 5"
183 lbs
25.5" x 25.5" × 36"
205 lbs




- (1) WATER IN: 3 3/16" 4 12/16" 3/4"
- (2) WATER OUT: 18 14/16" 2 9/16" 15/16"
- (3) ELECTRICAL CONNECTIONS: 2 11/16" 11 7/16"

BIN200

Compatible With Production/24h* Production/24h** **Bin Capacity** Dimensions (L × W × H) Net weight Ship Dim. (L × W × H) Ship weight

Power

_
G280A HC
_
_
440 lbs
31" x 34" × 39.5"
163 lbs
33" x 36.25" x 47.5"
205 lbs



Adjustable feet 3 15/16" - 6 15/16"

*Ambient Temperature 21°C (70°F) / Water 10°C (50°F) **Ambient Temperature 32°C (90°F) / Water 21°C (70°F)







Energy Verified

Warranty

3 years parts & labor,

5 years on the compressor