

R 2 B Ultra



<b>D</b>	Number of meals per service	10 to 20
	Quantity per batch in cutter function	Up to 2.2 lbs

**A SALES FEATURES**

The R 2 B Ultra Bowl Cutter Mixer is ideal for grinding, mincing and kneading, as well as for making mousses, emulsions and smooth stuffings. It effortlessly performs even the lengthiest task in just a few minutes, consistently producing a flawless end product.

**B TECHNICAL FEATURES**

R 2 B Ultra Bowl Cutter Mixer. Single phase 120V/60/1. Power 1HP. Speed: 1725 rpm. 2.9 L cutter bowl in stainless steel and smooth bowl-base blade assembly. 10 to 20 meals. Select your options at the back page, **F** part.

**C TECHNICAL DATA**

<b>Output power</b>	1 HP
<b>Electrical data</b>	120V/60/1 - 7 Amp
<b>Speed</b>	1725 rpm
<b>Dimensions (WxDxH)</b>	16 9/16" x 11" x 8 11/16"
<b>Rate of recyclability</b>	95%
<b>Net weight</b>	30 lbs
<b>Nema #</b>	5-15P
<b>Reference</b>	R 2 B Ultra 120V/60/1

**E PRODUCT FEATURES / BENEFITS**

**MOTOR BASE**

- Direct drive induction motor (no belt) for intensive use.
- Power 1HP
- Stainless steel motor shaft.
- Motor base made from heavy-duty composite material.
- Manual reset.
- **Speed:** 1725 rpm.
- **Pulse** button for better cut precision.

**CUTTER FUNCTION**

- 2.9 L stainless-steel cutter bowl with handle for better grip
- Bowl-base high resistance smooth blade assembly for homogeneous processing even for small amounts
- Central lid opening for adding liquid or solid ingredients during processing
- High heat- and shock-resistant see-through lid to monitor processing from start to finish
- All parts are dishwasher-safe and can easily be removed for cleaning

**ACCESSORIES INCLUDED**

- Cutter attachment: lid, bowl, and high resistance stainless steel smooth blade assembly with removable cap.

**STANDARDS**

ETL electrical and sanitation Listed/ cETL (Canada)



R 2 B Ultra

**F** OPTIONAL ACCESSORIES

- Coarse serrated blade assembly for kneading and grinding, ref 27138
- Fine serrated blade assembly for chopping herbs and spices, ref 27061
- Cuisine Kit ref 27395



Coarse-serrated



Fine-serrated

**G** ELECTRICAL DATA

120V/60/1 - delivered with cord and plug

