

UNDERCOUNTER HIGH TEMPERATURE
GLASSWASHER & SANITIZER

H29E-A



60 years of experience with evolving technology has produced the HANDY H29E-A. Thesis offers a professional wash system, designed and created to provide excellent cleaning, hygiene and brightness. The H29E-A is simple to use for heavy duty applications with low maintenance. It's your perfect solution for cleaning and sanitizing glasses, cups, mugs, cutlery and more. We guarantee an impeccable wash quality, which can meet even the needs of the most sophisticated customers.

Functions and benefits without compromise, all with lower running costs and at a very reasonable price.

Ecoclean: Water control system for partial clean water refill in every wash cycle.

Stainless steel: Adjustable rotation speed rinse arms, integral tank filter, with detergent injector welded to the tank.

ETL Sanitation: Programmed to guarantee the perfect sanitation result at high rinse temperatures.

LCD controls: Simple digital control panel with digital temperature display for intuitive and user-friendly operation.

High-quality products built using durable stainless steel with electromechanical components. The H29E-A is designed for energy savings with lower water and detergent consumption.



Intertek



Intertek

Dealer Stamp:

H29E-A

Technical features

- Control panel with LCD display
- ETL Sanitation to guarantee a powerful wash and sanitization with a high rinse temperature
- EWC System, electronic control with 4 individual programmable cycles
- Built in drain pump with Ecology Care system for partial refilling of clean water in every washing cycle
- Vacuum breaker valve
- Integral stainless steel tank filter + New filtering group for suction and drain
- Racks supplied: 1 dish basket, 1 glass basket, and 2 cutlery trays
- 1-year parts and labour warranty
- Adjustable 3L/hour detergent dispenser
- Adjustable 0.3L/hour rinse-aid dispenser
- 48 racks/hour or approximately 42 racks/hour in accordance with NSF standards

Uses standard racks	14" x 14" (400 x 400mm)
Door clearance	12.2" (310mm) height
Wash pump	1/3HP
Tank heating element	2.6kW, capacity: 4.5gal (17L)
Booster heating element	2.5kW, capacity: 0.9gal (3.2L)
Power	2.79kW, 208/220V 60Hz, 15A 1PH
Hot water requirements	½ GPC (2.6LPC) 125°F (55°C), will operate with cold water at reduced capacity
Water line requirements	¾" (or ½" with ¾" NPT terminal) hose supplied
Water pressure requirements	30–45psi (2–3bar)
Drain line	1" (25mm) connection hose supplied
Dimensions	18½"W x 21¾"D x 38"H (470W x 555D x 710H mm)
Weight	86lbs (39kg)
Shipping dimensions	26½"W x 22½"D x 34½"H (670W x 700D x 880H mm)
Shipping weight	105lbs (48kg)

